

ARCHER CHIEF GASOLINE ENGINE OIL



Archer Chief Gasoline Engine Oil is blended using specially selected, high quality base oils and additives that provide excellent detergency, dispersancy, oxidation stability, rust and corrosion prevention, and foam suppression.

Archer's high-quality base oil has a naturally high viscosity index that protects against hot and cold weather extremes. Oxidation inhibitors control oil thickening; detergents and dispersants reduce harmful deposits; and anti-wear agents minimize wear during cold weather startup and severe stop-and-go driving conditions.

This product is designed for older passenger car and light duty truck engines. It is formulated to protect against sludge, varnish, rust and acids.

TYPICAL SPECIFICATION DATA

ARCHER CHIEF GASOLINE ENGINE OIL				
SAE GRADE	10W	20W	30	40
Viscosity @ 100°C (cSt)	6.4	7.0	10.7	14.3
Viscosity @ 40°C (cSt)	35.5	40.0	85.0	135.5
Viscosity Index	133	136	110	104
Density (lb/gal)	7.21	7.24	7.30	7.41
CCS Viscosity (cP)	3,000	1,000	NA	NA
Pour Point (°C)	-36	-36	-30	-27
Pour Point (°F)	-33	-33	-22	-17
Flash Point (°C)	201	220	230	242
Flash Point (°F)	394	428	446	468
TBN	12.0	13.5	9.0	11.0
Sulfated Ash (% wt)	1.0	1.0	0.8	1.0

Meets or Exceeds:

- API SN, API SN Plus
- Chrysler MS-6395
- JAMA Member OEMs

ARCHER CHIEF SAE 10W	
Package Size	Item Number
5 Gal.	192449

ARCHER CHIEF SAE 20W	
Package Size	Item Number
5 Gal.	192485

ARCHER CHIEF SAE 30			
Package Size	Item Number	Package Size	Item Number
12 x 1 Qt.	191063	30 Gal.	191064
5 Gal.	191065		

ARCHER CHIEF SAE 40			
Package Size	Item Number	Package Size	Item Number
5 Gal.	191068	55 Gal.	191069