ARCHER SUPREME 10W-40 GASOLINE ENGINE OIL



Archer Supreme 10W-40 Heavy Duty Gasoline Engine Oil provides outstanding protection for those older engines requiring a multi-viscosity engine oil. It provides excellent flowability in colder climates and controls high-temperature volatility.

Archer Supreme 10W-40 uses a blend of Group II and Group II+ base oils that deliver excellent oxidation protection. It is also blended with a high-performing viscosity modifier technology to protect engine components during cold starts as well as high temperature operating conditions.

TYPICAL SPECIFICATION DATA

| ARCHER SUPREME 10W-40 GASOLINE ENGINE OIL | | | |
|---|--------|--|--|
| SAE GRADE | 10W-40 | | |
| Viscosity @ 100°C (cSt) | 14.5 | | |
| Viscosity @ 40°C (cSt) | 100.0 | | |
| Viscosity Index | 150 | | |
| Density (lb/gal) | 7.21 | | |
| CCS Viscosity (cP) | 6,000 | | |
| Pour Point (°C) | -33 | | |
| Pour Point (°F) | -27 | | |
| Flash Point (°C) | 223 | | |
| Flash Point (°F) | 433 | | |
| TBN | 10.0 | | |
| Sulfated Ash (% wt) | 0.9 | | |

Meets or exceeds:

- API SN, API SN Plus
- Chrysler MS-6395
- JAMA

| ARCHER SUPREME 10W-40 | | | |
|-----------------------|-------------|--------------|-------------|
| Package Size | Item Number | Package Size | Item Number |
| 5 Gal. | 191159 | 30 Gal. | 191158 |